



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	G	L1	L2	L3	ΦD1	↗
APLL04-G01	4	G1/8	5.5	36.3	19	11.5	14
APLL04-G02	4	G1/4	7.5	38.3	19	11.5	17
APLL06-G01	6	G1/8	5.5	37.7	19.2	13.5	14
APLL06-G02	6	G1/4	7.5	40.2	19.2	13.5	17
APLL06-G03	6	G3/8	7.5	41.7	19.2	13.5	20
APLL06-G04	6	G1/2	10	45.7	19.2	13.5	24
APLL08-G01	8	G1/8	5.5	42.3	22.5	15	14
APLL08-G02	8	G1/4	7.5	44.3	22.5	15	17
APLL08-G03	8	G3/8	7.5	46	22.5	15	20
APLL08-G04	8	G1/2	10	48.3	22.5	15	24
APLL10-G01	10	G1/8	5.5	53.8	27.8	19	17
APLL10-G02	10	G1/4	7.5	54.3	27.8	19	17
APLL10-G03	10	G3/8	7.5	54.3	27.8	19	20
APLL10-G04	10	G1/2	10	57.8	27.8	19	24
APLL12-G01	12	G1/8	5.5	56.5	29.5	21.5	21
APLL12-G02	12	G1/4	7.5	59	29.5	21.5	21
APLL12-G03	12	G3/8	7.5	59.5	29.5	21.5	21
APLL12-G04	12	G1/2	10	62.5	29.5	21.5	24