




Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	L3	ΦD1	✚
APB04-M5	4	M5	3.5	21.3	38	11.5	10
APB04-M6	4	M6	4	21.8	38	11.5	10
APB04-01	4	R1/8	7.5	23.8	38	11.5	10
APB04-02	4	R1/4	9.5	26.8	38	11.5	14
APB04-03	4	R3/8	10.5	28.3	38	11.5	17
APB06-M5	6	M5	3.5	21.7	39	13.5	12
APB06-M6	6	M6	4	22.2	39	13.5	12
APB06-01	6	R1/8	7.5	24.2	39	13.5	12
APB06-02	6	R1/4	9.5	26.7	39	13.5	14
APB06-03	6	R3/8	10.5	28.2	39	13.5	17
APB06-04	6	R1/2	13.5	31.7	39	13.5	21
APB08-01	8	R1/8	7.5	27.5	45	15	14
APB08-02	8	R1/4	9.5	29.5	45	15	14
APB08-03	8	R3/8	10.5	31	45	15	17
APB08-04	8	R1/2	13.5	34.5	45	15	21
APB10-01	10	R1/8	7.5	32.8	57	19	17
APB10-02	10	R1/4	9.5	34.8	57	19	17
APB10-03	10	R3/8	10.5	35.8	57	19	17
APB10-04	10	R1/2	13.5	39.3	57	19	21
APB12-01	12	R1/8	7.5	33.5	59	21.5	21
APB12-02	12	R1/4	9.5	36	59	21.5	21
APB12-03	12	R3/8	10.5	37	59	21.5	21
APB12-04	12	R1/2	13.5	40	59	21.5	21
APB14-03	14	R3/8	10.5	41	54	23.5	22
APB14-04	14	R1/2	13.5	44	54	23.5	22
APB15-03	15	R3/8	10.5	44	66	26.5	24
APB15-04	15	R1/2	13.5	47	66	26.5	24
APB16-03	16	R3/8	10.5	44	66	26.5	24
APB16-04	16	R1/2	13.5	47	66	26.5	24
APB16-06	16	R3/4	15	49	66	26.5	27