



## Features

- \*One-touch tube fittings are used in pneumatic piping.
- \*The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- \*Even after installation, the direction of the tube can be changed freely.
- \*Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- \*All R and NPT threads are pre-coated sealant.

## Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm <sup>2</sup> (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	○	✚
APC04-M5	4	M5	3.5	20.7	2	10
APC04-M6	4	M6	4	20.8	2	10
APC04-01	4	R1/8	7.5	20.2	3	10
APC04-02	4	R1/4	9.5	18.2	3	14
APC04-03	4	R3/8	10.5	19.1	3	17
APC06-M5	6	M5	3.5	21.3	2	12
APC06-M6	6	M6	4	21	2	12
APC06-01	6	R1/8	7.5	20.3	4	12
APC06-02	6	R1/4	9.5	22.4	4	14
APC06-03	6	R3/8	10.5	20.2	4	17
APC06-04	6	R1/2	13.5	24.8	4	21
APC08-01	8	R1/8	7.5	25.8	5	14
APC08-02	8	R1/4	9.5	24.7	5	14
APC08-03	8	R3/8	10.5	21.2	6	17
APC08-04	8	R1/2	13.5	25.2	6	21
APC10-01	10	R1/8	7.5	29.8	5	17
APC10-02	10	R1/4	9.5	30.8	6	17
APC10-03	10	R3/8	10.5	28.2	8	17
APC10-04	10	R1/2	13.5	26.3	8	21
APC12-01	12	R1/8	7.5	31.2	5	21
APC12-02	12	R1/4	9.5	32.7	6	21
APC12-03	12	R3/8	10.5	29.7	8	21
APC12-04	12	R1/2	13.5	32.2	8	21
APC14-03	14	R3/8	10.5	34	8	22
APC14-04	14	R1/2	13.5	33	10	22
APC15-03	15	R3/8	10.5	37	8	24
APC15-04	15	R1/2	13.5	35	10	24
APC16-03	16	R3/8	10.5	36.1	8	24
APC16-04	16	R1/2	13.5	38.2	10	24
APC16-06	16	R3/4	15	41		27