



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	$\Phi D1$	⚙
APCF04-M5	4	M5	5.5	21	10	10
APCF04-M6	4	M6	6	21.5	10	10
APCF04-01	4	Rc1/8	8.5	24	10	14
APCF04-02	4	Rc1/4	11	26.5	10	17
APCF06-M5	6	M5	5.5	21.5	12	12
APCF06-M6	6	M6	6	22	12	12
APCF06-01	6	Rc1/8	8.5	24.5	12	14
APCF06-02	6	Rc1/4	11	27	12	17
APCF06-03	6	Rc3/8	12	28	12	21
APCF06-04	6	Rc1/2	14	30	12	24
APCF08-01	8	Rc1/8	8.5	26	14	14
APCF08-02	8	Rc1/4	11	28.5	14	17
APCF08-03	8	Rc3/8	12	29.5	14	21
APCF08-04	8	Rc1/2	14	31.5	14	24
APCF10-01	10	Rc1/8	8.5	29.5	17	17
APCF10-02	10	Rc1/4	11	32.7	17	17
APCF10-03	10	Rc3/8	12	33	17	21
APCF10-04	10	Rc1/2	14	35.7	17	24
APCF12-01	12	Rc1/8	8.5	31	20	21
APCF12-02	12	Rc1/4	11	33.5	20	21
APCF12-03	12	Rc3/8	12	34.5	20	21
APCF12-04	12	Rc1/2	14	36.5	20	24
APCF16-03	16	Rc3/8	12	36.5	24	24
APCF16-04	16	Rc1/2	14	38.5	24	24