



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	L3	L4	ΦD1	↻
APH04-M5	4	M5	3.5	10.7	17.3	20.5	11.5	8
APH04-01	4	R1/8	7.5	15	23	23.5	11.5	12
APH04-02	4	R1/4	9.5	16.8	26.3	25.5	11.5	14
APH06-M5	6	M5	3.5	11.7	17.3	22	13.5	8
APH06-01	6	R1/8	7.5	15	23	23.5	13.5	12
APH06-02	6	R1/4	9.5	16.2	26.3	25.4	13.5	14
APH06-03	6	R3/8	10.5	19	31.9	29.5	13.5	19
APH08-01	8	R1/8	7.5	15.7	23	26.5	15	12
APH08-02	8	R1/4	9.5	17.5	26.3	28.9	15	14
APH08-03	8	R3/8	10.5	19	31.9	29.8	15	19
APH08-04	8	R1/2	13.5	24	38.6	32.5	15	24
APH10-01	10	R1/8	7.5	18	23	30.5	19	12
APH10-02	10	R1/4	9.5	19.5	26.3	32.6	19	14
APH10-03	10	R3/8	10.5	21	31.9	33	19	19
APH10-04	10	R1/2	13.5	24.2	38.6	36	19	24
APH12-02	12	R1/4	9.5	20.8	26.3	33.5	21.5	14
APH12-03	12	R3/8	10.5	22.2	31.9	35.5	21.5	19
APH12-04	12	R1/2	13.5	25.5	38.6	36.5	21.5	24