



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	ΦD1	L	L1	L2	L3	H1	H2	ΦD2	ΦD3
APKJ04	4	4	75	19	42	22	19	9	13.5	3.2
APKJ06	6	6	79	19	42	26	20.5	9	15	3.2
APKJ08	8	8	99	20.5	48	29	24	11	19	3.2
APKJ10	10	10	114.5	24.5	60.8	36.8	28.5	11	18.4	3.2
APKJ06-04	4	6	75	19	36	22	19	8	13.5	3.2
APKJ08-04	4	8	76.5	20.5	36	22	19	8	13.5	3.2
APKJ08-06	6	8	80.5	20.5	42	26	20.5	9	15	3.2
APKJ10-06	6	10	103.5	24.5	61	29	24	11	19	4.2
APKJ10-08	8	10	103.5	24.5	61	29	24	11	19	4.2