



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	ΦD1	ΦD2	ΦD3	L1	L2	L3	L4
APYJ04	4	4	11.5	3.2	52.5	33.5	14.5	11
APYJ06	6	6	13.5	3.2	53.8	34.8	15	13
APYJ08	8	8	15	3.2	57.8	37.3	18	15
APYJ10	10	10	19	4.2	71	46.5	21	18
APYJ12	12	12	21.5	4.2	75.5	49.5	21.5	21
APYJ06-04	4	6	11.5	3.2	52.8	33.8	14.5	11
APYJ08-06	6	8	13.5	3.2	55.5	35	15	13
APYJ10-08	8	10	15	3.2	62	37.3	18	15
APYJ12-10	10	12	19	4.2	72.5	46.5	21	18