



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	ΦD1	ΦD2	L1	L2	L3
APZ04	4	11.5	3.2	38	14	7
APZ06	6	13.5	3.2	39	16	8
APZ08	8	15	3.2	45	18	9
APZ10	10	19	4.2	57	24	12
APZ12	12	21.5	4.3	59	27	13.5

MODEL	ΦD	ΦD1	ΦD2	L1	L2	L3
APZ5/32	5/32	11.5	3.2	38	14	7
APZ1/4	1/4	13.5	3.2	39	16	8
APZ5/16	5/16	15	3.2	45	18	9
APZ3/8	3/8	19	4.2	57	24	12
APZ1/2	1/2	21.5	4.3	59	27	13.5