



## Features

- \*One-touch tube fittings are used in pneumatic piping.
- \*The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- \*Even after installation, the direction of the tube can be changed freely.
- \*Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- \*All R and NPT threads are pre-coated sealant.

## Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm <sup>2</sup> (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	L3	L4	ΦD1	ΦD2	↻
APX04-M5	4	M5	3.5	11	40	14.5	11.5	3.2	10
APX04-M6	4	M6	4	11	40.5	14.5	11.5	3.2	10
APX04-01	4	R1/8	7.5	11	42.5	14.5	11.5	3.2	10
APX04-02	4	R1/4	9.5	11	45.5	14.5	11.5	3.2	14
APX04-03	4	R3/8	10.5	11	47	14.5	11.5	3.2	17
APX06-M5	6	M5	3.5	13	41.5	15	13.5	3.2	12
APX06-M6	6	M6	4	13	42	15	13.5	3.2	12
APX06-01	6	R1/8	7.5	13	44	15	13.5	3.2	12
APX06-02	6	R1/4	9.5	13	46.5	15	13.5	3.2	14
APX06-03	6	R3/8	10.5	13	48	15	13.5	3.2	17
APX08-01	8	R1/8	7.5	15	46.5	18	15	3.2	14
APX08-02	8	R1/4	9.5	15	48.5	18	15	3.2	14
APX08-03	8	R3/8	10.5	15	50	18	15	3.2	17
APX08-04	8	R1/2	13.5	15	53.5	18	15	3.2	21
APX10-01	10	R1/8	7.5	18	56.5	21	19	4.2	17
APX10-02	10	R1/4	9.5	18	58.5	21	19	4.2	17
APX10-03	10	R3/8	10.5	18	59.5	21	19	4.2	17
APX10-04	10	R1/2	13.5	18	63	21	19	4.2	21
APX12-01	12	R1/8	7.5	21	59.5	21.5	21.5	4.2	21
APX12-02	12	R1/4	9.5	21	62	21.5	21.5	4.2	21
APX12-03	12	R3/8	10.5	21	63	21.5	21.5	4.2	21
APX12-04	12	R1/2	13.5	21	66	21.5	21.5	4.2	21