







































Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ϕD	Rc	L	L1	L2	$\phi D1$			M
APMF04-01	4	Rc1/8	24	8.5	6	10			M12X1
APMF04-02	4	Rc1/4	26.5	11	6	10			M12X1
APMF06-01	6	Rc1/8	24.8	8.5	7	12			M14X1
APMF06-02	6	Rc1/4	29.5	11	7	12			M14X1
APMF06-03	6	Rc3/8	30.5	12	7	12			M14X1
APMF06-04	6	Rc1/2	33	14	7	12			M14X1
APMF08-01	8	Rc1/8	26.5	8.5	7.5	14			M16X1
APMF08-02	8	Rc1/4	32	11	7.5	14			M16X1
APMF08-03	8	Rc3/8	34.3	12	7.5	14			M16X1
APMF08-04	8	Rc1/2	36.5	14	7.5	14			M16X1
APMF10-01	10	Rc1/8	30	8.5	9.5	17			M20X1
APMF10-02	10	Rc1/4	32.5	11	9.5	17			M20X1
APMF10-03	10	Rc3/8	34	12	9.5	17			M20X1
APMF10-04	10	Rc1/2	38	14	9.5	17			M20X1
APMF12-01	12	Rc1/8	31.5	8.5	10	20			M22X1
APMF12-02	12	Rc1/4	34	11	10	20			M22X1
APMF12-03	12	Rc3/8	35	12	10	20			M22X1
APMF12-04	12	Rc1/2	37	14	10	20			M22X1