




Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L	L2	L3	ΦD1	ΦD2	H1	H2	✎
APKD04-M5	4	M5	3.5	66	42	22	13	3.2	19	9	10
APKD04-01	4	R1/8	7.5	68.5	42	22	13	3.2	19	9	10
APKD04-02	4	R1/4	9.5	71.5	42	22	13	3.2	19	9	14
APKD04-03	4	R3/8	10.5	72.5	42	22	13	3.2	19	9	17
APKD06-M5	6	M5	3.5	67	42	26	14.5	3.2	20.5	9	10
APKD06-01	6	R1/8	7.5	70	42	26	14.5	3.2	20.5	9	12
APKD06-02	6	R1/4	9.5	72	42	26	14.5	3.2	20.5	9	14
APKD06-03	6	R3/8	10.5	73	42	26	14.5	3.2	20.5	9	17
APKD06-04	6	R1/2	13.5	76.5	42	26	14.5	3.2	20.5	9	21
APKD08-01	8	R1/8	7.5	89	48	29	18.4	3.2	24	11	14
APKD08-02	8	R1/4	9.5	91	48	29	18.4	3.2	24	11	14
APKD08-03	8	R3/8	10.5	92.5	48	29	18.4	3.2	24	11	17
APKD08-04	8	R1/2	13.5	96	48	29	18.4	3.2	24	11	21
APKD10-01	10	R1/8	7.5	100	60.8	36.8	18.4	4.2	28.5	11	17
APKD10-02	10	R1/4	9.5	102	60.8	36.8	18.4	4.2	28.5	11	17
APKD10-03	10	R3/8	10.5	103	60.8	36.8	18.4	4.2	28.5	11	17
APKD10-04	10	R1/2	13.5	106.5	60.8	36.8	18.4	4.2	28.5	11	21