



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	L3	L4	ΦD1	↻
APD04-M5	4	M5	3.5	21.3	40.3	19	11.5	10
APD04-M6	4	M6	4	21.8	40.8	19	11.5	10
APD04-01	4	R1/8	7.5	23.8	42.8	19	11.5	10
APD04-02	4	R1/4	9.5	26.8	45.8	19	11.5	14
APD04-03	4	R3/8	10.5	28.3	47.3	19	11.5	17
APD06-M5	6	M5	3.5	21.7	40.9	19.2	13.5	12
APD06-M6	6	M6	4	22.2	41.4	19.2	13.5	12
APD06-01	6	R1/8	7.5	24.2	43.4	19.2	13.5	12
APD06-02	6	R1/4	9.5	26.7	46	19.2	13.5	14
APD06-03	6	R3/8	10.5	28.2	47.5	19.2	13.5	17
APD06-04	6	R1/2	13.5	31.7	51	19.2	13.5	21
APD08-01	8	R1/8	7.5	27.5	50	22.5	15	14
APD08-02	8	R1/4	9.5	29.5	52	22.5	15	14
APD08-03	8	R3/8	10.5	31	53.5	22.5	15	17
APD08-04	8	R1/2	13.5	34.5	57	22.5	15	21
APD10-01	10	R1/8	7.5	33	61.5	27.8	19	17
APD10-02	10	R1/4	9.5	35	63.5	27.8	19	17
APD10-03	10	R3/8	10.5	36	64.5	27.8	19	17
APD10-04	10	R1/2	13.5	39.5	68	27.8	19	21
APD12-01	12	R1/8	7.5	33.5	63	29.5	21.5	21
APD12-02	12	R1/4	9.5	36	65.5	29.5	21.5	21
APD12-03	12	R3/8	10.5	37	66.5	29.5	21.5	21
APD12-04	12	R1/2	13.5	40	69.5	29.5	21.5	21
APD14-03	14	R3/8	10.5	40	70	30	23.5	22
APD14-04	14	R1/2	13.5	43	73	30	23.5	22
APD15-03	15	R3/8	10.5	44	77	33	26.5	24
APD15-04	15	R1/2	13.5	47	80	33	26.5	24
APD16-03	16	R3/8	10.5	44	77	33	26.5	24
APD16-04	16	R1/2	13.5	47	80	33	26.5	24
APD16-06	16	R3/4	15	49	82	33	26.5	27