



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ϕD	R	L1	L2	$\phi D1$	\odot
APOC04-M5	4	M5	3.5	20.7	10	2
APOC04-M6	4	M6	4	20.8	10	2
APOC04-01	4	R1/8	7.5	20.2	10	3
APOC04-02	4	R1/4	9.5	18.2	14	3
APOC06-M5	6	M5	3.5	21.3	12	2
APOC06-M6	6	M6	4	21	12	2
APOC06-01	6	R1/8	7.5	20.5	12	4
APOC06-02	6	R1/4	9.5	22.4	14	4
APOC06-03	6	R3/8	10.5	20.5	17	4
APOC06-04	6	R1/2	13.5	24.8	21	4
APOC08-01	8	R1/8	7.5	25.8	14	5
APOC08-02	8	R1/4	9.5	24.7	14	5
APOC08-03	8	R3/8	10.5	21.2	17	6
APOC08-04	8	R1/2	13.5	25.2	21	6
APOC10-01	10	R1/8	7.5	29.8	17	5
APOC10-02	10	R1/4	9.5	30.8	17	6
APOC10-03	10	R3/8	10.5	28.2	17	8
APOC10-04	10	R1/2	13.5	26.3	21	8
APOC12-01	12	R1/8	7.5	31.2	21	5
APOC12-02	12	R1/4	9.5	32.7	21	6
APOC12-03	12	R3/8	10.5	29.7	21	8
APOC12-04	12	R1/2	13.5	32.2	21	8
APOC16-03	16	R3/8	10.5	36.1	24	8
APOC16-04	16	R1/2	13.5	38.2	24	10