



Features

- *One-touch tube fittings are used in pneumatic piping.
- *The tube fittings come in a wide variety of models to meet all your needs in pneumatic piping.
- *Even after installation, the direction of the tube can be changed freely.
- *Nickel-Plated metal body ensures anti-corrosion and anti-contamination.
- *All R and NPT threads are pre-coated sealant.

Specifications

Fluid Type	Air (No other type of gas or liquid)	
Working Pressure Range	0~150PSI	0~9.9Kgf/cm ² (0~990KPa)
Negative Pressure	-29.5 in Hg	-750mm Hg(10 Torr)
Working Temperature	32~140°F	0~60°C

MODEL	ΦD	R	L1	L2	L3	ΦD1	🔧
APLF04-M5	4	M5	5.5	19.5	19	11.5	10
APLF04-M6	4	M6	6	20	19	11.5	10
APLF04-01	4	Rc1/8	8.5	23.3	19	11.5	14
APLF04-02	4	Rc1/4	11	25.8	19	11.5	17
APLF06-M5	6	M5	5.5	19.2	19.2	13.5	12
APLF06-M6	6	M6	6	19.7	19.2	13.5	12
APLF06-01	6	Rc1/8	8.5	22.7	19.2	13.5	14
APLF06-02	6	Rc1/4	11	25.7	19.2	13.5	17
APLF06-03	6	Rc3/8	12	27.2	19.2	13.5	21
APLF08-01	8	Rc1/8	8.5	25	22.5	15	14
APLF08-02	8	Rc1/4	11	28.5	22.5	15	17
APLF08-03	8	Rc3/8	12	30	22.5	15	21
APLF10-02	10	Rc1/4	11	32.3	27.8	19	17
APLF10-03	10	Rc3/8	12	33.8	27.8	19	21
APLF10-04	10	Rc1/2	14	36.8	27.8	19	24
APLF12-02	12	Rc1/4	11	34.5	29.5	21.5	21
APLF12-03	12	Rc3/8	12	35.5	29.5	21.5	21
APLF12-04	12	Rc1/2	14	38	29.5	21.5	24